



Laying Pebble Mesh Tiles

Laying Pebbles Mesh Tiles - A Step-by-Step Guide



1) Gather your Pebble Mesh Tile Installation tools - a Sponge, 1/2" V Notch Trowel, Grout Float, Stiff Brush, Sealant (if required, knee pads and Heavy Duty Gloves



2) Apply the mastic (usually Thinset or Quikset) with the trowel first using the flat side and then followed by using the notches to ensure an even coat.



3) Place the Pebble Mesh Tile onto the mastic. Be sure the edges of each tile are as close together as possible to ensure a seamless look.



4) Use the grout float to apply even pressure to the pebble tile and press them onto the mastic - take care not to press so hard that the mastic oozes up between the individual stones.





Laying Pebble Mesh Tiles



5) Use a sanded grout on 1 m² sections at a time until the entire area is covered. For ease of use we recommend pre-mixed grout.



6) Allow the grout to set for not longer than 30 minutes. After this time use the stiff brush to remove any excess grout and reveal as much of the top of the stones as you desire.



7) Use the sponge to continue to remove grout until you achieve the look you want. Once the grout has setup completely according to the manufacturers instructions we recommend re-sealing in order to protect both the pebbles and the grout.

For more information about our range of quality Pebble Mesh Tiles, please:

- visit us at www.tuscanpath.com.au
- Visit your nearest Bunnings store (our Range is available Australia wide)
 - Contact us on (03)8339 0250. We're always here to help!

Please Note: While we have taken every care to ensure the accuracy of this DIY information, Tuscan Path cannot be held responsible for any of the advice contained in our website and where appropriate we advise you to consult a professional.

-2-



Suppliers of the finest local and imported
Pots • Pebbles • Pavers • Garden Decor